
TERYX KRX® 1000









20.3 ft

351 lb

781 lb

N/A

14.6 x 33.1 x 9.1 in

POWER

Engine 4-stroke, DOHC, 8-valve parallel-twin, liquid cooled

Displacement

76.7 lb-ft @ 7,000 rpm **Maximum Torque**

Bore x Stroke 92.0 x 75.1mm

Compression Ratio

Fuel System DFI® with (2) 50mm throttle bodies

Ignition TCBI with Electronic Advance

Starting System Electric

Transmission Automatic CVT with centrifugal clutch (H,L,N,R)

Final Drive Selectable 2WD/4WD with locking front differential, shaft

Engine Braking

DETAILS

Lighting

Frame

Turning Radius

Cargo Bed Load

Payload Capacity

Seating Capacity

Towing Capacity

Capacity

Dimensions (LxWxH)

Ladder type, tubular steel

(2) LED headlights, (2) LED taillights, LED stoplight

Overall Length 130.1 in

Overall Width 68.1 in

Overall Height 74.8 in

Curb Weight 1,894.1 lb* / 1,896.3 lb* CA Model

Wheelbase

Instruments Multi-function digital meter with bar-style tachometer (2 display options), digital speedometer, bar-style fuel gauge,

gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning lamp, and CVT belt warning

Additional Features Steel skid-plates w/ drain holes

Color Choices Metallic Sierra Blue/Super Black, Metallic Light Gray/Super

Warranty 6 Month Limited Warranty

CAPABILITY

Front Suspension / Wheel Travel

Double wishbone, Showa 2.5 shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable compression damping/18.6 in

Rear Suspension / **Wheel Travel**

4-link trailing-arm rear suspension, Showa 2.5 shocks with piggyback reservoir, fully adjustable preload, and 24position adjustable compression damping/21.1 in

Maxxis® Carnivore 31 x 10.00R15 8PR **Front Tires Rear Tires** Maxxis® Carnivore 31 x 10.00R15 8PR

Steering Electric Power Steering (EPS) / rack-and-pinion

Front Brakes Dual hydraulic discs with 2-piston calipers

Dual hydraulic discs with single-piston calipers **Rear Brakes**

Ground Clearance 14.8 in (max) / 14.2 in (std)

Fuel Capacity 10.6 gal

Scan with camera to view videos. key features and more.

