TERYX KRX® 1000 LIFTED EDITION







14.6 x 33.1 x 9.1 in

351 lb

781 lb

N/A

D	N	١	N	E	D
		м	N	г	π

Engine 4-stroke, DOHC, 8-valve parallel-twin, liquid cooled

Displacement 999cc

Maximum Torque 76.7 lb-ft @ 7,000 rpm

Bore x Stroke 92.0 x 75.1mm

Compression Ratio 11.

Fuel System DFI® with (2) 50mm throttle bodies

Ignition TCBI with Electronic Advance

Starting System Electric

Transmission Automatic CVT with centrifugal clutch (H,L,N,R)

Final Drive Selectable 2WD/4WD with locking front differential, shaft

Engine Braking Yes

Lighting

Cargo Bed

Capacity

Dimensions (LxWxH)

Cargo Bed Load

Payload Capacity

Seating Capacity

Towing Capacity

Frame Ladder type, tubular steel

Overall Length 132.9 in

Overall Width 68.1 in
Overall Height 75.4 in

Curb Weight 2,006.6 lb* / 2,008.8 lb* CA Model

Wheelbase 98.8 in

Instruments Multi-function digital meter with bar-style tachometer (2

(2) LED headlights, (2) LED taillights, LED stoplight

display options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning lamp, and CVT belt warning lamp

Additional Features Elevated snorkel intakes and CVT exhaust duct, Wide fender

flares, Front Bumper, F/R Tow Hooks, Steel skid-plates w/ drain holes, Rear view mirror, WARN® VRX 45-S Powersport

Winch

Color Choices Lime Green/Super Black

Warranty 6 Month Limited Warranty

CAPABILITY

Front Suspension / Wheel Travel

Double wishbone, FOX 2.5 PODIUM LSC shocks with piggyback reservoir, fully adjustable preload, and 24-position

adjustable compression damping/18.6 in

Rear Suspension / Wheel Travel 4-link trailing-arm rear suspension, FOX 2.5 PODIUM LSC shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable compression damping/21.1 in

Front Tires ITP Cryptid 32 x 10.00R15 6PR

Rear Tires ITP Cryptid 32 x 10.00R15 6PR

Steering Electric Power Steering (EPS) / rack-and-pinion

Front Brakes Dual hydraulic discs with 2-piston calipers

Rear Brakes Dual hydraulic discs with single-piston calipers

Ground Clearance 15.0 in (max), 14.4 in (std)

Fuel Capacity 10.6 gal
Turning Radius 20.3 ft

Scan with camera to view videos, key features and more.

