

2025

TERYX KRX® 1000 TRAIL EDITION

Kawasaki

Let the Good Times Roll®



CYPHER CAMO GRAY/SUPER BLACK



| POWER                           |                                                                                                                                                                           | Cargo Bed Dimensions (LxWxH) |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|---------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Engine                          | 4-stroke, DOHC, 8-valve parallel-twin, liquid cooled                                                                                                                      | Cargo Bed Load Capacity      | 351 lb                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Displacement                    | 999cc                                                                                                                                                                     | Payload Capacity             | 781 lb                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Maximum Torque                  | 76.7 lb-ft @ 7,000 rpm                                                                                                                                                    | Seating Capacity             | 2                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Bore x Stroke                   | 92.0 x 75.1mm                                                                                                                                                             | Towing Capacity              | N/A                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Compression Ratio               | 11.5:1                                                                                                                                                                    | Lighting                     | (2) LED headlights, (2) LED taillights, LED stoplight                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Fuel System                     | DFI® with (2) 50mm throttle bodies                                                                                                                                        | DETAILS                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Ignition                        | TCBI with Electronic Advance                                                                                                                                              | Frame                        | Ladder type, tubular steel                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Starting System                 | Electric                                                                                                                                                                  | Overall Length               | 133.3 in                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Transmission                    | Automatic CVT with centrifugal clutch (H,L,N,R)                                                                                                                           | Overall Width                | 68.1 in                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Final Drive                     | Selectable 2WD/4WD with locking front differential, shaft                                                                                                                 | Overall Height               | 76.6 in                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Engine Braking                  | Yes                                                                                                                                                                       | Curb Weight                  | 2,017.6 lb* / 2,019.8 lb* CA Model                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| CAPABILITY                      |                                                                                                                                                                           | Wheelbase                    | 98.8 in                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Front Suspension / Wheel Travel | Double wishbone, FOX 2.5 PODIUM LSC shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable compression damping/18.6 in                     | Instruments                  | Multi-function digital meter with bar-style tachometer (2 display options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning lamp, and CVT belt warning lamp |
| Rear Suspension / Wheel Travel  | 4-link trailing-arm rear suspension, FOX 2.5 PODIUM LSC shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable compression damping/21.1 in | Additional Features          | KQR™ Sport Roof, Front Bumper, Rear Bumper, Nerf Bars, Steel skid-plates w/ drain holes, WARN® VRX 45 Powersport Winch                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Front Tires                     | Maxxis® Carnivore 31 x 10.00R15 8PR                                                                                                                                       | Color Choices                | Metallic Sierra Blue/Super Black, Metallic Light Gray/Super Black                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Rear Tires                      | Maxxis® Carnivore 31 x 10.00R15 8PR                                                                                                                                       | Warranty                     | 6 Month Limited Warranty                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Steering                        | Electric Power Steering (EPS) / rack-and-pinion                                                                                                                           |                              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Front Brakes                    | Dual hydraulic discs with 2-piston calipers                                                                                                                               |                              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Rear Brakes                     | Dual hydraulic discs with single-piston calipers                                                                                                                          |                              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Ground Clearance                | 14.2 in (max) / 13.6 in (std)                                                                                                                                             |                              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Fuel Capacity                   | 10.6 gal                                                                                                                                                                  |                              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Turning Radius                  | 20.3 ft                                                                                                                                                                   |                              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |

Scan with camera  
to view videos,  
key features  
and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit hawaii.kawasaki.com for full product details.