

2025

TERYX[®] KRX4[™] 1000 BLACKOUT EDITION



| POWER | | Cargo Bed Dimensions (LxWxH) | |
|---------------------------------|---|------------------------------|--|
| Engine | 4-stroke, DOHC, 8-valve parallel-twin, liquid cooled | Cargo Bed Load Capacity | 14.6 x 33.1 x 9.1 in |
| Displacement | 999cc | Payload Capacity | 351 lb |
| Maximum Torque | 76.7 lb-ft @ 7,000 rpm | Seating Capacity | 1,001 lb |
| Bore x Stroke | 92.0 x 75.1mm | Towing Capacity | 4 |
| Compression Ratio | 11.5:1 | Lighting | N/A |
| Fuel System | DFI [®] with (2) 50mm throttle bodies | | (2) LED headlights, (2) LED taillights, LED stoplight, (4) LED light bars |
| Ignition | TCBI with Electronic Advance | DETAILS | |
| Starting System | Electric | Frame | Ladder type, tubular steel |
| Transmission | Automatic CVT with centrifugal clutch (H,L,N,R) | Overall Length | 160.4 in |
| Final Drive | Selectable 2WD/4WD with locking front differential, shaft | Overall Width | 68.1 in |
| Engine Braking | Yes | Overall Height | 78.0 in |
| | | Curb Weight | 2,253.5 lb* / 2,257.7 lb* CA Model |
| CAPABILITY | | Wheelbase | 125.8 in |
| Front Suspension / Wheel Travel | Double wishbone, FOX 2.5 PODIUM LSC shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable compression damping/18.6 in | Instruments | Multi-function digital meter with bar-style tachometer (2 display options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning lamp, and CVT belt warning lamp |
| Rear Suspension / Wheel Travel | 4-link trailing-arm rear suspension, FOX 2.5 PODIUM LSC shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable compression damping/21.1 in | Additional Features | LED light bars (38-in mounted to front of roof, 8-in mounted to front bumper, (2) 8-in mounted to rear of roof), Front Bumper, Rear Bumper, Steel skid-plates w/ drain holes, KQR [™] Premium Roof, Hifonics [®] Audio System, WARN [®] VRX 45 Powersport Winch |
| Front Tires | Maxxis [®] Carnivore 31 x 10.00R15 8PR | Color Choices | Flat Ebony |
| Rear Tires | Maxxis [®] Carnivore 31 x 10.00R15 8PR | Warranty | 6 Month Limited Warranty |
| Steering | Electric Power Steering (EPS) / rack-and-pinion | | |
| Front Brakes | Dual hydraulic discs with 2-piston calipers | | |
| Rear Brakes | Dual hydraulic discs with single-piston calipers | | |
| Ground Clearance | 13.8 in (max), 13.2 in (std) | | |
| Fuel Capacity | 10.6 gal | | |
| Turning Radius | 23.3 ft | | |

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx[®] side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit hawaii.kawasaki.com for full product details.