2025 VERSYS[®] 1100 SE ABS





METALLIC GRAPHITE GRAY/METALLIC DIABLO BLACK



POWER

Engine	4-stroke, in-line 4-cylinder, DOHC, liquid-cooled
Displacement	1,099сс
Bore x Stroke	77.0 x 59.0mm
Compression Ratio	11.8:1
Maximum Horsepower	133.0 hp1 @ 9,000 rpm
Maximum Torque	82.5 lb-ft @ 7,600 rpm
Fuel System	DFI® with 38mm throttle bodies (4)
Ignition	TCBI with Electronic Advance
Transmission	6-speed, return shift with wet multi-disc manual Assist & Slipper Clutch
Final Drive	Chain
Electronic Rider Aids	Economical Riding Indicator, Electronic Cruise Control, Kawasaki TRaction Control (KTRC), Kawasaki Electronic Control Suspension (KECS), Kawasaki Intelligent anti-lock Brake System (KIBS), Anti-lock Brake System (ABS), Power Modes, Kawasaki Cornering Management Function (KCMF), Kawasaki Quick Shifter (KQS), IMU-Enhanced Chassis Orientation Awareness

Front Tire120/70-17Rear Tire180/55-17Front BrakesDual 310mm petal discs with radial-mount 4-piston
monobloc calipers, Kawasaki Intelligent anti-lock Brake
System (KIBS)Rear BrakesSingle 260mm petal disc with single-piston caliper,
Kawasaki Intelligent anti-lock Brake System (KIBS)

DETAILS

	Frame Type	Twin-tube, aluminum
	Rake/Trail	27.0°/4.0 in
	Overall Length	89.4 in
	Overall Width	37.4 in
	Overall Height	60.2 in (windshield Hi) / 59.8 in (windshield Lo)
	Ground Clearance	5.9 in
	Seat Height	33.1 in
	Estimated Dry Weight	520.4 lb** (+20 lb w/ saddlebags)
	Curb Weight	571.1 lb* (+20 lb w/ saddlebags)
l	Fuel Capacity	5.5 gal
	Wheelbase	59.8 in
	Special Features	Full-color TFT Instrumentation, All-LED lighting including Cornering Lights, USB Type-C outlet, Adjustable windshield, Grip heaters and hand guards, ERGO-FIT®, Highly Durable Paint, Smartphone Connectivity with Voice Command via RIDEOLOGY THE APP MOTORCYCLE
	Color Choices	Metallic Graphite Gray/Metallic Diablo Black
	Warranty	24 Month Limited Warranty

PERFORMANCE

Front Suspension / Wheel Travel	43mm inverted Showa fork with KECS-controlled rebound and compression damping, manual spring preload adjustability and top-out springs/5.9 in
Rear Suspension / Wheel Travel	Horizontal back-link, Showa BFRC Lite gas-charged shock with piggyback reservoir, KECS-controlled compression and rebound damping electronically-adjustable spring preload/5.9 in

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). 'This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit hawaii.kawasaki.com for full product details.