

2026

KLX[®]300R



- LIME GREEN
- BRIGHT WHITE

POWER		Front Brakes	Single 270mm petal disc with a dual-piston caliper
Engine	4-stroke, single-cylinder, DOHC, liquid-cooled	Rear Brakes	Single 240mm petal disc with single-piston caliper
Displacement	292cc	DETAILS	
Bore x Stroke	78.0 x 61.2mm	Frame Type	Semi-double cradle
Compression Ratio	11.0:1	Rake/Trail	26.9° / 4.3 in
Fuel System	DFI [®] with 34mm Keihin throttle body	Overall Length	86.6 in
Ignition	TCBI with electronic advance	Overall Width	32.5 in
Transmission	6-speed, return shift with wet multi-disc manual clutch	Overall Height	49.0 in
Final Drive	Chain	Ground Clearance	11.8 in
PERFORMANCE		Seat Height	35.4 in
Front Suspension / Wheel Travel	43mm inverted telescopic fork with adjustable compression damping/11.2 in	Estimated Dry Weight	264.6 lb** / 269.0 lb** 50-State Model
Rear Suspension / Wheel Travel	Uni-Trak [®] gas charged shock with piggyback reservoir with adjustable compression, rebound damping and spring preload/11.2 in	Curb Weight	282.2 lb* / 286.7 lb* 50-State Model
Front Tire	3.0 x 21	Fuel Capacity	2.1 gal
Rear Tire	4.6 x 18	Wheelbase	56.5 in
		Color Choices	Lime Green, Bright White
		Warranty	6 Month Limited Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit hawaii.kawasaki.com for full product details.