MULE 4000 TRANS™









POWER

Engine 4-stroke, 2-cylinder, OHV, 90° V-twin, Liquid-cooled

Displacement 617cc

Maximum 20.0 hp1 @ 3,600 rpm

Horsepower

Maximum Torque 34.7 lb-ft @ 2,500 rpm

Bore x Stroke 76.0 x 68.0mm

Compression Ratio 10:3:1

Fuel System DFI® with 34mm Mikuni throttle body

Transmission Continuously Variable Transmission (CVT) with (H,N,R)

2WD, shaft. Dual mode rear differential with differential **Final Drive**

lock

Engine Braking No

Alternator Output 23 amp

(max)

Front Brakes Drum

Rear Brakes Drum **Ground Clearance** 7.7 in

Fuel Capacity 6.3 gal

Turning Radius 12.8 ft

50.4 x 47.6 x 11.2 in (2-person) / 30.3 x 47.6 x 11.2 in (4-**Cargo Bed**

Dimensions (LxWxH) person)

Cargo Bed Load

Capacity

800 lb (2-person) / 401 lb (4-person)

Payload Capacity 1,330 lb

Seating Capacity 2-4

Towing Capacity 1,200 lb

Lighting (2) Halogen headlights, (2) tail/brake lights

CAPABILITY

Front Suspension / MacPherson Strut/3.9 in Wheel Travel

Rear Suspension / **Wheel Travel**

DeDion Axle/2.8 in

Front Tires 23 x 11-10 **Rear Tires** 23 x 11-10

Steering Rack-and-pinion

Park Brake Type Independent, mechanical drum

DETAILS

Overall Length 128.5 in **Overall Width** 58.5 in **Overall Height** 75.8 in

Estimated Dry

Weight

1,448.7 lb**

Curb Weight 1,514.8 lb* Wheelbase 85.2 in

Instruments

Parking brake warning light, coolant temperature warning

light, 12V DC outlet, fuel gauge, hour meter

Color Choices Timberline Green

Scan with camera to view videos, key features and more.



Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). 1This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

All MULE™ 4000/4010 and MULE 4000/4010 TRANS™ Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of SAE J1194. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit hawaii.kawasaki.com for full product details.