

2026

TERYX[®] KRX4[™] 1000

Kawasaki

Let the Good Times Roll[®]



- SMOKY GRAY/SUPER BLACK
- GRAYISH BLUE/SUPER BLACK

POWER			
Engine	4-stroke, DOHC, 8-valve parallel-twin, liquid cooled	Turning Radius	23.3 ft
Displacement	999cc	Cargo Bed Dimensions (LxWxH)	14.6 x 33.1 x 9.1 in
Maximum Horsepower	110.0 hp ¹ @ 8,500 rpm	Cargo Bed Load Capacity	351 lb
Maximum Torque	75.2 lb-ft @ 7,000 rpm	Payload Capacity	1,001 lb
Bore x Stroke	92.0 x 75.1mm	Seating Capacity	4
Compression Ratio	11.5:1	Towing Capacity	N/A
Fuel System	DFI [®] with (2) 50mm throttle bodies	Lighting	(2) LED headlights, (2) LED taillights, LED sto
Ignition	TCBI with electronic advance		
Starting System	Electric		
Transmission	Automatic CVT with centrifugal clutch (H,L,N,R)		
Final Drive	Selectable 2WD/4WD with locking front differential, shaft		
Engine Braking	Yes		
CAPABILITY		DETAILS	
Front Suspension / Wheel Travel	Double wishbone, Showa 2.5 shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable compression damping/18.6 in	Frame	Ladder type, tubular steel
Rear Suspension / Wheel Travel	4-link trailing-arm rear suspension, Showa 2.5 shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable compression damping/21.1 in	Overall Length	157.3 in
Front Tires	Maxxis [®] Carnivore 31 x 10.00R15 8PR	Overall Width	68.1 in
Rear Tires	Maxxis [®] Carnivore 31 x 10.00R15 8PR	Overall Height	76.2 in
Steering	Electric Power Steering (EPS) / rack-and-pinion	Estimated Dry Weight	1,997.7 lb** / 1,999.9 lb** CA Model
Front Brakes	258mm dual hydraulic discs with 2-piston calipers	Curb Weight	2,099.2 lb* / 2,101.4 lb* CA Model
Rear Brakes	258mm dual hydraulic discs with single-piston calipers	Wheelbase	125.8 in
Ground Clearance	14.8 in (max), 14.2 in (std)	Instruments	Multi-function digital meter with bar-style tachometer (2 display options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning lamp, and CVT belt warning lamp
Fuel Capacity	10.6 gal	Additional Features	Steel skid-plates w/ drain holes
		Color Choices	Smoky Gray/Super Black, Grayish Blue/Super Black
		Warranty	6 Month Limited Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx[®] side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2026 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit hawaii.kawasaki.com for full product details.