

2026

VERSYS® 650 ABS

Kawasaki

Let the Good Times Roll®



POWER		Rear Tire	160/60 ZR-17
Engine	4-stroke, 2-cylinder, DOHC, liquid-cooled, 4 valves per cylinder parallel twin	Front Brakes	Dual 300mm petal-style discs with 2-piston calipers, ABS
Displacement	649cc	Rear Brakes	Single 250mm petal-style disc with single-piston caliper, ABS
Bore x Stroke	83.0 x 60.0mm	DETAILS	
Compression Ratio	10.8:1	Frame Type	Double pipe diamond frame constructed from high-tensile steel
Maximum Torque	44.8 lb-ft	Rake/Trail	25° / 4.3 in
Fuel System	DFI® with 38mm Keihin throttle bodies (2)	Overall Length	85.2 in
Ignition	TCBI with electronic advance	Overall Width	33.1 in
Transmission	6-speed with positive neutral finder	Overall Height	53.5 in/55.9 in (windshield down/up)
Final Drive	Sealed chain	Ground Clearance	6.7 in
PERFORMANCE		Seat Height	33.3 in
Front Suspension / Wheel Travel	41mm hydraulic telescopic fork with stepless adjustable rebound and preload/5.9 in	Curb Weight	482.9 lb*
Rear Suspension / Wheel Travel	Single offset laydown shock with remote adjustable spring preload/5.7 in	Fuel Capacity	5.5 gal
Front Tire	120/70 ZR-17	Wheelbase	55.7 in
		Color Choices	Metallic Deep Blue/Metallic Spark Black
		Warranty	12 month limited warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit hawaii.kawasaki.com for full product details.