## 2020 **KX**<sup>™</sup>**100**







### **POWER**

Engine	2-stroke single with exhaust power valve, liquid-cooled
Displacement	99cc
Bore x Stroke	52.5 x 45.8mm
Compression Ratio	10.2:1 (low speed) - 8.7:1 (high speed)
Fuel System	28mm Keihin carburetor
Ignition	CDI with digital advance
Transmission	6-speed, return shift, with wet multi-disc manual clutch
Final Drive	Chain

# PERFORMANCE

Front Suspension / Wheel Travel	36mm inverted telescopic cartridge fork with 20-way compression damping/10.8 in
Rear Suspension / Wheel Travel	Uni-Trak® gas charged shock with piggyback reservoir with 24-way compression and 21-way rebound damping plus adjustable spring preload/10.8 in
Front Tire	70/100-19

Rear Tire	90/100-16
Front Brakes	Single 220mm petal disc with dual-piston caliper
Rear Brakes	Single 220mm petal disc with single-piston caliper

### **DETAILS**

	Frame Type	High-tensile steel perimeter design withsubframe member
	Rake/Trail	29°/4.3 in
	Overall Length	75.6 in
	Overall Width	30.1 in
	Overall Height	45.3 in
	Ground Clearance	13.0 in
	Seat Height	34.3 in
n	Curb Weight	169.7 lb*
	Fuel Capacity	1.32 gal
ng	Wheelbase	51.6 in
	Color Choices	Lime Green
	Warranty	Not Available



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit hawaii.kawasaki.com for full product details.