





_	_	-		_	_
D	П	17	м		D
		w	w		м
	u		•	_	

Engine 4-stroke single, DOHC, liquid-cooled

Displacement 449cc

Bore x Stroke 96.0 x 62.1mm

Compression

Ratio

12.5:1

Fuel System DFI® with 44mm Keihin throttle body

Ignition Digital CDI with electric start

Transmission 5-speed, return shift, with wet multi-disc

manual clutch and hydraulic clutch actuation

Final Drive Chain

PERFORMANCE

Front 49mm inverted telescopic coil-spring fork with 16-way compression damping and 16-way rebound damping/12.0 in

Rear Uni-Trak® gas charged shock with piggyback

reservoir with dual-range (4 turns stepless high speed/19-way low-speed) compression damping, 38-way rebound damping and

adjustable preload/12.1 in

Front Tire 80/100-21

Rear Tire 120/80-19

Front Brakes Single semi-floating 270mm Braking® petal disc with dual-piston caliper

Rear Brakes Single 250mm Braking® petal disc with single-

piston caliper

DETAILS

Frame Type Aluminum perimeter

Rake/Trail 27.6°/4.8 in

Overall Length 86.0 in

Overall Width 32.7 in

Overall Height 50.2 in

Ground 13.4 in

Clearance

Plus™

(optional)

Seat Height 37.6 in

Curb Weight 232.3 lb without fuel / 242.4 lb*

Fuel Capacity 1.64 gal

Wheelbase 58.5 in

Color Choices Lime Green

Warranty Not Available

Kawasaki Not Available
Protection



Suspension /

Wheel Travel

