

# 2020 KX™ 65

**Kawasaki**  
Let the Good Times Roll®



 LIME GREEN



## POWER

<b>Engine</b>	2-stroke single with exhaust power valve, liquid-cooled
<b>Displacement</b>	64cc
<b>Bore x Stroke</b>	45.5 x 41.6mm
<b>Compression Ratio</b>	8.4:1
<b>Fuel System</b>	24mm Mikuni carburetor
<b>Ignition</b>	CDI with digital advance
<b>Transmission</b>	6-speed, return shift, with wet multi-disc manual clutch
<b>Final Drive</b>	Chain

<b>Rear Tire</b>	80/100-12
<b>Front Brakes</b>	Single 180mm disc with single-piston caliper
<b>Rear Brakes</b>	Single 180mm disc with single-piston caliper

## PERFORMANCE

<b>Front Suspension / Wheel Travel</b>	33mm leading axle telescopic fork with 4-way rebound damping/8.3 in
<b>Rear Suspension / Wheel Travel</b>	Uni-Trak® single shock system with 4-way rebound damping and fully adjustable spring preload/9.4 in
<b>Front Tire</b>	60/100-14

## DETAILS

<b>Frame Type</b>	Tubular, semi-double cradle
<b>Rake/Trail</b>	27° / 2.4 in
<b>Overall Length</b>	62.6 in
<b>Overall Width</b>	29.9 in
<b>Overall Height</b>	37.6 in
<b>Ground Clearance</b>	12.0 in
<b>Seat Height</b>	29.9 in
<b>Curb Weight</b>	132.2 lb*
<b>Fuel Capacity</b>	1.0 gal
<b>Wheelbase</b>	44.1 in
<b>Color Choices</b>	Lime Green
<b>Warranty</b>	Not Available

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [hawaii.kawasaki.com](http://hawaii.kawasaki.com) for full product details.