2020

MULE[™] 4000









POWER

Engine 4-stroke, 2-cylinder, OHV 90° V Liquid-cooled, gas

Displacement 617cc

Maximum Torque 34.7 lb-ft @ 2500 rpm

Bore x Stroke 2.99x2.68 in

Compression Ratio 10:3:1

Fuel System DFI® with 34mm Mikuni throttle body

Transmission Continuously Variable Transmission (CVT) with (H,N,R)

Final Drive 2WD, shaft. Dual mode rear differential with

differential lock

Engine Braking No

Alternator Output 23 amp

(max)

Rear Brakes Drum

Ground Clearance 7.5 in

Fuel Capacity 6.3 gal

Turning Radius 11.0 ft

Cargo Bed Dimensions (LxWxH) 46.3 x 51.6 x 11.4 in

Cargo Bed Load

Capacity

800 lb 1327 lb

Payload Capacity

Seating Capacity

Towing Capacity

1200 lb

Lighting

(2) Halogen headlights, (2) tail/brake lights,(2)

Halogen tail/brake lights

CAPABILITY

Front Suspension / MacPherson Strut/3.9 in Wheel Travel

Rear Suspension / Wheel Travel

DeDion Axle/2.8 in

Front Tires

23x11.00-10

Rear Tires

23x11.00-10

Steering

Rack-and-pinion

Park Brake Type

Independent, Mechanical Drum

Front Brakes

Drum

DETAILS

Overall Length 116.7 in

Overall Width 62.0 in

Overall Height 75.8 in

Curb Weight 1338.4 lb*

Wheelbase 73.6 in

Instruments

Parking brake warning light, coolant temperature warning light, 12V DC outlet, fuel gauge, hour meter

Color Choices

Timberline Green, Dark Royal Red

Warranty

Kawasaki 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

