
MULE PRO-DXT™ EPS DIESEL









POWER

Engine 4-stroke, 3-cylinder, OHV, liquid-cooled, diesel

Displacement 993cc

Maximum Torque 38.3 lb-ft @ 2400 rpm

Bore x Stroke 2.91x3.03 in

Compression Ratio

Fuel System Bosch in-line injection pump

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

Double wishbone/8.5 (L) /8.7 (R) in

with differential lock

Engine Braking

Alternator Output (max)

55 amp

CAPABILITY

Front Suspension / Double wishbone/8.7 in

Rear Suspension /

Wheel Travel

Front Tires

Wheel Travel

26x9.00-12

Rear Tires 26x11.00-12

Steering Electric Power Steering (EPS), Tilt steering

Park Brake Type Independent, Mechanical Disc

Front Brakes Dual Disc, 2 piston caliper

Rear Brakes Dual Disc, 1 piston caliper **Ground Clearance** 10.2 in

Fuel Capacity 7.9 gal 16.0 ft

Turning Radius

Cargo Bed 42.7 x 53.7 x 11.0 in (3-person)22.0 x 53.7 x 11.0 in (6-**Dimensions**

(LxWxH) **Cargo Bed Load**

Capacity

1000 lb (3-person)350 lb (6-person)

Payload Capacity 1581 lb

Seating Capacity 3-person (1 row), 6 person (2 row)

Towing Capacity

Lighting (2) Halogen headlights, (2) Halogen tail/brake lights

DETAILS

Overall Length 133.3 in

Overall Width 64.0 in

Overall Height 77.6 in

1936.0 lb* **Curb Weight**

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer,

> fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, glow plug indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt reminder

Color Choices Timberline Green, Bright White

Warranty Kawasaki 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

