
2020

MULE PRO-FXR™









POWER

Engine 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas

Displacement 812cc

Maximum Torque 48.0 lb-ft @ 3500 rpm

Bore x Stroke 2.83x2.62 in

Compression Ratio 9.5:1

Fuel System DFI® with 34mm throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking

Alternator Output 75 amp

(max)

Ground Clearance 10.8 in

Fuel Capacity 7.9 gal **Turning Radius** 14.0 ft

Cargo Bed

Dimensions (LxWxH)

Cargo Bed Load

Capacity

Payload Capacity

Seating Capacity

Towing Capacity

Lighting

1000 lb (600 lb for California models)

1616 lb (1264 lb California model)

2000 lb

(2) Halogen headlights, (2) LED headlights, (2) Halogen

tail/brake lights

37.6 x 53.3 x 11.0 in

CAPABILITY

Front Suspension / **Wheel Travel**

Double wishbone/8.7 in

Rear Suspension / **Wheel Travel**

Double wishbone/8.5 (L) /8.7 (R) in

Front Tires 27x9.00-12, radial

27x11.00-12, radial

Rear Tires Steering

Electric Power Steering (EPS), Tilt steering

Park Brake Type

Independent, Mechanical Disc

Front Brakes

Dual Disc, 2 piston caliper

Rear Brakes

Dual Disc, 1 piston caliper

DETAILS

Overall Length 121.5 in

Overall Width 64.0 in

Overall Height 77.2 in

Curb Weight 1768.4 lb*

Wheelbase 79.7 in

Instruments Multi-function display includes digital speedometer,

> fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt

reminder lamps

Color Choices Metalic Phantom Silver, Candy Persimmon Red

Kawasaki 3-Year Limited Warranty Warranty



