MULE PRO-FXT™ EPS









POWER

Engine 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas

Displacement 812cc

Maximum Torque 48.0 lb-ft @ 3500 rpm

Bore x Stroke 2.83x2.62 in

Compression Ratio

Fuel System DFI® with 34mm throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking

Alternator Output

(max)

75 amp

CAPABILITY

Front Suspension / Double wishbone/8.7 in **Wheel Travel**

Rear Suspension / **Wheel Travel**

Double wishbone/8.5 (L) /8.7 (R) in

Front Tires

26x9.00-12, radial

Rear Tires

Steering

Park Brake Type

Independent, Mechanical Disc

Front Brakes

Dual Disc, 2 piston caliper Dual Disc, 1 piston caliper

Rear Brakes

26x11.00-12, radial Electric Power Steering (EPS), Tilt steering

Warranty

10.2 in

Fuel Capacity 7.9 gal

Turning Radius

Cargo Bed

Dimensions (LxWxH)

Cargo Bed Load

Ground Clearance

Capacity

Payload Capacity

Seating Capacity

Towing Capacity

Lighting

16.0 ft

42.7 x 53.7 x 11.0 in (3-person)22.0 x 53.7 x 11.0 in (6-

1000 lb (3-person)350 lb (6-person)(600 lb for

California models)

1616 lb (1264 lb California model)

3-person (1 row), 6 person (2 row)

2000 lb

(2) Halogen headlights, (2) Halogen tail/brake lights

DETAILS

Overall Length 133.3 in

Overall Width 64.0 in

Overall Height 77.6 in

Curb Weight 1911.7 lb*

Wheelbase 92.3 in

Instruments

Multi-function display includes digital speedometer,

fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators,

seatbelt reminder lamps

Color Choices Timberline Green, Bright White

Kawasaki 3-Year Limited Warranty



