²⁰²⁰ **MULE SX**[™]







Rear Brakes

DETAILS

Overall Length



Drum

106.7 in

POWER

4-stroke, single-cylinder, OHV, air-cooled, gas
401cc
20.6 lb-ft @ 2200 rpm
3.23x2.99 in
8.3:1
Nikki 6C1026 carburetor
Continuously Variable Transmission (CVT) with (H,N,R)
2WD, shaft. Dual mode rear differential with differential lock
Νο
17 amp

Kedi Didkes	Diulli
Ground Clearance	6.1 in
Fuel Capacity	4.2 gal
Turning Radius	10.8 ft
Cargo Bed Dimensions (LxWxH)	35.6 x 40.9 x 9.6 in
Cargo Bed Load Capacity	400 lb
Payload Capacity	926 lb
Seating Capacity	2
Towing Capacity	1100 lb*
Lighting	(2) Halogen headlights,(2) Halogen tail/brake lights

CAPABILITY

Front Suspension / Wheel Travel	MacPherson Strut/3.1 in	Overall Width	52.6 in
wheet havet		Overall Height	70.1 in
Rear Suspension / Wheel Travel	Unit Swingarm/3.1 in	Curb Weight	967.6 lb**
Front Tires	22x9.00-10	Wheelbase	70.1 in
Rear Tires	22x11.00-10	Instruments	Fuel gauge, hour meter, oil temp light, parking brake light
Steering	Rack-and-pinion	Color Choices	Timberline Green, Dark Royal Red
Park Brake Type	Independent, Mechanical Drum		, ,
Front Brakes	Drum	Warranty	Kawasaki 3-Year Limited Warranty

Scan with camera to view videos, key features and more.



*Requires Optional Hitch

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit hawaii.kawasaki.com for full product details.