## NINJA® 650 ABS KRT EDITION







n	1	П	M		
r	u	ľ	N	r	ĸ

**Engine** 4-stroke, Parallel Twin, DOHC, liquid-cooled

**Displacement** 649cc

Bore x Stroke 83.0 x 60.0mm

Compression

Ratio

47.0 lb-ft

10.8:1

Maximum Torque

Fuel System

DFI® with dual 36mm Keihin throttle bodies

Ignition

TCBI with electronic advance

**Transmission** 

6-speed

**Final Drive** 

Sealed chain

**Electronic Rider** 

Aids

ABS

## **PERFORMANCE**

Front Suspension / Wheel Travel	41mm hydraulic telescopic fork/4.9 in
Rear Suspension / Wheel Travel	Horizontal back-link with adjustable spring preload/5.1 in
Front Tire	120/70x17
Rear Tire	160/60x17

Front Brakes Dual 300mm petal-type discs and 2-piston calipers and ABS

Rear Brakes Single 220mm petal-type disc and singlepiston caliper and ABS

## **DETAILS**

Frame Type Tubular, Diamond

5.1

**Rake/Trail** 24.0/3.9

Overall Length 80.9

Overall Width 29.1

Overall Height 45.1

Ground

Clearance

Seat Height 31.1

Curb Weight 423.4 lb\*

Fuel Capacity 4.0 gal

Wheelbase 55.5

**Special Features** TFT Instrumentation

Color Choices

Lime Green/Ebony

12 Month Limited Warranty

Warranty

Kawasaki Protection Plus™ (optional) 12, 24, 36 or 48 months

Scan with camera to view videos, key features and more.

