2020 **VULCAN® 1700 VAQUERO® ABS**







POWER

		Rear Tire		
Engine	4-stroke, 52° V-twin, liquid-cooled	Front Brakes		
Displacement	1,700cc/103.7 cu in			
Bore x Stroke	102.0 x 104.0mm	Rear Brakes		
Compression	9.5:1			
Ratio		DETAILS		
Maximum	107.6 lb-ft @ 2750 rpm			
Torque		Frame Type		
Fuel System	DFI® 42mm throttle bodies (2)			
Ignition	TCBI with digital advance	Overall Lengt		
Transmission	6-speed with overdrive and positive neutral finder	Overall Width		
		Overall Heigh		
Final Drive	Carbon fiber-reinforced belt	Ground		
Clearance				

Front Tire 130/90x16 170/70x16 Dual 300mm discs, dual four-piston calipers, K-ACT II ABS Single 300mm disc, twin-piston caliper, K-ACT II ABS

ive	Frame Type	Steel, double-cradle with box-section single-tube backbone	
	Overall Length	98.8 in	
	Overall Width	38.2 in	
	Overall Height	50.8 in	
	Ground Clearance	5.7 in	
	Seat Height	28.7 in	
shocks, in	Curb Weight	844.5 lb*	
	Fuel Capacity	5.3 gal	
	Wheelbase	65.6 in	
	Color Choices	Candy Imperial Blue	
	Warranty	36 Month Limited Warranty	

PERFORMANCE

Front Suspension / Wheel Travel 45mm hydraulic fork/5.5 in

Rear

Swingarm with twin air-assisted sl with 4-way rebound damping/3.1

Suspension / Wheel Travel

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit hawaii.kawasaki.com for full product details.