







POWER

Engine 4-stroke, 4-cylinder, DOHC, 4-valve, liquid-cooled,

supercharged

Displacement 998cc

Bore x Stroke 76.0 x 55.0mm

Compression

Ratio

Maximum Torque 101.0 lb-ft

Fuel System DFI® with 36mm Keihin throttle bodies

Ignition TCBI with electronic advance

11 2.1

Transmission 6-speed dog-ring, return shift

Final Drive Sealed chain

Electronic Rider

Aids

Integrated Riding Modes, Kawasaki Cornering Management Function (KCMF), Power Modes (3), Kawasaki Launch Control Mode (KLCM), Kawasaki Traction Control (KTRC), Kawasaki Launch Control Mode (KLCM), Kawasaki Engine Brake Control (KEBC), Kawasaki Intelligent anti-lock Brake System (KIBS), Kawasaki Quick Shifter (KQS) (upshift &

downshift), Electronic Cruise Control

PERFORMANCE

Front Suspension / Wheel Travel

Showa SFF-BP Fork with Adjustable Compression and Rebound Damping, Spring Preload Adjustability

Rear Suspension / Wheel Travel New Uni-Trak®, Showa Gas-Charged Shock with Adjustable Compression and Rebound Damping,

Preload Adjustability

Front Tire 120/70-17

Rear Tire 190/55-17

Front Brakes Dual Disc w/Radial-mount M4.32 Calipers, ABS

Rear Brakes Single 260mm petal-style disc with single piston

caliper, ABS

DETAILS

Overall Height

Frame Type Trellis, high tensile steel

44.5 in

Rake/Trail 24.9°/4.1in

Overall Length 82.1 in

Overall Width 31.9 in

Ground Clearance 5.5 in

Seat Height 32.7 in

Curb Weight 527.0 lb*

Fuel Capacity 5.0 gal

Wheelbase 57.3 in

Special Features Rideology the App Smartphone Connectivity, TFT

Instrumentation

Color Choices Metallic Spark Black/Metallic Graphite Gray/Mirror

Coated Spark Black

Warranty 12 Month Limited Warranty



