





_	_			
n	n	M	ı	R
$\boldsymbol{\nu}$		w	•	• к
		-	,	-

**Engine** 2-stroke single, liquid-cooled

**Displacement** 64cc

**Bore x Stroke** 45.5 x 41.6mm

Compression

8.4:1 **Ratio** 

Ignition CDI with digital advance

6-speed, return shift, with wet multi-disc **Transmission** 

manual clutch

### 24mm Mikuni carburetor **Fuel System**

### **Final Drive** Chain

# **PERFORMANCE**

**Front** Suspension / **Wheel Travel**  33mm leading axle telescopic fork with 4way rebound damping/8.3 in

Rear Suspension / **Wheel Travel**  Uni-Trak® single shock system with 4-way rebound damping and fully adjustable spring preload/9.4 in

**Front Tire** 60/100-14

Single 180mm disc with single-piston **Front Brakes** 

caliper

80/100-12

**Rear Brakes** Single 180mm disc with single-piston

caliper

# **DETAILS**

**Rear Tire** 

High-tensile steel semi-double cradle **Frame Type** 

Rake/Trail 27°/2.4 in

**Overall Length** 62.6 in

**Overall Width** 29.9 in

**Overall Height** 37.6 in

Ground 12.0 in Clearance

**Seat Height** 29.9 in

**Curb Weight** 132.2 lb\*

**Fuel Capacity** 1.0 gal

Wheelbase 44.1 in

**Color Choices** Lime Green

Not Available Warranty



