## **MULE 4000 TRANS™**









## **POWER**

Engine 4-stroke, 2-cylinder, OHV, 90° V, liquid-cooled

Displacement 617cc

Maximum Torque 34.7 lb-ft @ 2500 rpm

Bore x Stroke 2.99x2.68 in

Compression Ratio 10:3:1

Fuel System DFI® with 34mm Mikuni throttle body

Transmission Continuously Variable Transmission (CVT) with (H,N,R)

Final Drive 2WD, shaft. Dual mode rear differential with

differential lock

Engine Braking No

Alternator Output 23 amp

(max)

1...1

Drum

**Ground Clearance** 7.7 in

Fuel Capacity 6.3 gal

Turning Radius 12.8 ft

Cargo Bed 50.4

Dimensions

**Rear Brakes** 

50.4 x 47.6 x 11.2 in (2-person)30.3 x 47.6 x 11.2 in (4-

ions

(LxWxH)

800 lb (2-person)400 lb (4-person)

Capacity

**Cargo Bed Load** 

Payload Capacity 1330 lb

Seating Capacity 2-4

Towing Capacity 1200 lb

Lighting (2) Halogen headlights (2) tail/brake lights

## **CAPABILITY**

Front Suspension / MacPherson Strut/3.9 in Wheel Travel

Rear Suspension / Wheel Travel

DeDion Axle/2.8 in

Front Tires

23x11.00-10

Rear Tires

**Steering** 

23x11.00-10

Park Brake Type

Electric Power Steering (EPS)
Independent, Mechanical Drum

Front Brakes

Drum

**DETAILS** 

Overall Length 128.5 in

Overall Width 58.5 in

Overall Height 78.1 in

Curb Weight 1514.1 lb\*

Wheelbase 85.2 in

Instruments

Parking brake warning light, coolant temperature warning light, 12V DC outlet, fuel gauge, hour meter

**Color Choices** 

**Bright White** 

Warranty

Kawasaki 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

