
MULE™ 4010 TRANS4x4®









Drum

7.1 in

6.3 gal

12.8 ft

POWER

Engine 4-stroke, 2-cylinder, OHV, 90° V Liquid-cooled

Displacement 617cc

Maximum Torque 34.7 lb-ft @ 2500 rpm

Bore x Stroke 2.99x2.68 in

Compression Ratio 10:3:1

Fuel System DFI® with 34mm Mikuni throttle body

Transmission Continuously Variable Transmission (CVT) with

(H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear

differential with differential lock

Engine Braking No

Alternator Output 23 amp

(max)

Dimensions (LxWxH) Cargo Bed Load Capacity

DETAILS

Overall Length

Cargo Bed

Rear Brakes

Fuel Capacity

Turning Radius

Ground Clearance

800 lb (2-person)400 lb (4-person)

50.4 x 47.6 x 11.2 in (2-person)30.3 x 47.6 x 11.2 in (4-

Payload Capacity 1330 lb

Seating Capacity 2-4

Towing Capacity 1200 lb

Lighting (2) Halogen headlights (2) tail/brake lights

CAPABILITY

Front Suspension / MacPherson Strut/3.9 in Wheel Travel

Rear Suspension / Wheel Travel

DeDion Axle/2.8 in

 Front Tires
 23x11.00-10

 Rear Tires
 23x11.00-10

Steering Electric Power Steering (EPS)

Park Brake Type Independent, Mechanical Drum

Front Brakes Drum

Overall Width
Overall Height
Curb Weight
Wheelbase
Instruments
Color Choices

Parking brake warning light, coolant temperature warning light, 12V DC outlet, fuel gauge, hour meter

olor Choices Timberline Green, Dark Royal Red

128.5 in

58.5 in

75.8 in

85.2 in

1587.6 lb*

Warranty Kawasaki 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

