MULE PRO-FXT™







ום	n	W	II		D
1	U	M	И	CI	м

Engine 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas

Displacement 812cc

Maximum Torque 48.0 lb-ft @ 3500 rpm

Bore x Stroke 2.83x2.62 in

Compression Ratio 9.5

Fuel System DFI® with 34mm throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking Ye

Alternator Output (max)

put 75 amp

CAPABILITY

Front Suspension / Double wishbone / 8.7 in Wheel Travel

Rear Suspension /

Wheel Travel

Double wishbone/8.5 (L) /8.7 (R) in

Front Tires 26x9.00-12, radial
Rear Tires 26x11.00-12, radial

Steering Rack-and-pinion

Park Brake Type Independent, Mechanical Disc

Front Brakes Dual Disc, 2 piston caliper

Rear Brakes Dual Disc, 1 piston caliper

Ground Clearance 10.2 in

Turning Radius 16.0 ft

Cargo Bed 42.7 x 53.7 x 11.0 in (3-person)22.0 x 53.7 x 11.0 in (6-

Cargo Bed Dimensions (LxWxH)

Fuel Capacity

person)

Cargo Bed Load 10

Capacity

1000 lb (3-person)350 lb (6-person)(600 lb for

California models)

7.9 gal

Payload Capacity 1616 lb

Seating Capacity 3-person (1 row), 6 person (2 row)

Towing Capacity 2000 lb

Lighting (2) Halogen headlights.

DETAILS

Overall Length 133.3 in

Overall Width 64.0 in

Overall Height 77.6 in

Curb Weight 1887.5 lb*

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer,

fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT warning indicator, neutral, reverse and parking indicators, seatbelt

reminder lamps

Color Choices Super Black

Warranty Kawasaki 3-Year Limited Warranty



