MULE PRO-FXT™ RANCH EDITION









POWER

Engine 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas

Displacement 812cc

Maximum Torque 48.0 lb-ft @ 3500 rpm

Bore x Stroke 2.83x2.62 in

Compression Ratio

Fuel System DFI® with 34mm throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking

Alternator Output

(max)

75 amp

CAPABILITY

Front Suspension / Double wishbone/8.7 in **Wheel Travel**

Rear Suspension / **Wheel Travel**

Rear Tires

Double wishbone/8.5 (L) /8.7 (R) in

Front Tires 26x9.00-12, radial

26x11.00-12, radial Steering Electric Power Steering (EPS), Tilt steering

Park Brake Type Independent, Mechanical Disc

Front Brakes Dual Disc, 2 piston caliper

Rear Brakes Dual Disc, 1 piston caliper **Ground Clearance** 10.0 in

Fuel Capacity 7.9 gal

Turning Radius 16.0 ft

Cargo Bed 42.7 x 53.7 x 11.0 in (3-person), 22.0 x 53.7 x 11.0 in (6-**Dimensions**

Cargo Bed Load Capacity

(LxWxH)

1000 lb (3-person), 350 lb (6-person), (600 lb for California models)

Payload Capacity 1574 lb

Seating Capacity 3-person (1 row), 6 person (2 row)

Towing Capacity

Lighting (2) Halogen headlights. (2) LED headlights

DETAILS

Overall Length 135.6 in

Overall Width 64.0 in

Overall Height 79.5 in

Curb Weight 1962 5 lh*

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer,

> fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators,

seatbelt reminder lamps

Color Choices Metallic Phantom Silver

Warranty Kawasaki 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

