2021 MULE SX[™] 4x4 XC LE FI







METALLIC ONYX BLACK



POWER

Engine	4-stroke, single-cylinder, OHV, air-cooled
Displacement	401cc
Maximum Torque	21.4 lb-ft @ 2400 rpm
Bore x Stroke	3.23x2.99 in
Compression Ratio	8.6:1
Fuel System	Fuel injection
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)
Final Drive	Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock
Engine Braking	Νο
Alternator Output (max)	22.9 amp

Rear Brakes	Drum
Ground Clearance	8.1 in
Fuel Capacity	4.2 gal
Turning Radius	11.8 ft
Cargo Bed Dimensions (LxWxH)	35.6 x 40.9 x 9.6 in
Cargo Bed Load Capacity	400 lb
Payload Capacity	884 lb
Seating Capacity	2
Towing Capacity	1100 lb*
Lighting	(4) LED headlights, tail/brake lights

DETAILS

CAPABILITY				
		Overall Length	106.7 in	
Front Suspension / Wheel Travel Rear Suspension /	MacPherson Strut/3.1 in Unit Swingarm/3.1 in	Overall Width Overall Height Curb Weight	52.6 in 75.0 in 1098.1 lb**	
Wheel Travel Front Tires	26x9.00-12	Wheelbase	70.1 in	
Rear Tires	26x9.00-12	Instruments	Fuel gauge, hour meter, oil temp light, parking brake light	
Steering	Rack-and-pinion, Tilt steering	Color Choices	Metallic Onyx Black	
Park Brake Type	Independent, Mechanical Drum	Warranty	Kawasaki 3-Year Limited Warranty	
Front Brakes	Drum			

*Requires Optional Hitch

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULETM side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit hawaii.kawasaki.com for full product details.

and more.

