





## **POWER**

Engine 4-stroke, SOHC, 4-valve V-twin, liquid-cooled

Displacement 783cc

Maximum Torque 47.0 lb-ft@ 5500 rpm

Bore x Stroke 85.0 x 69.0mm

Compression Ratio 10.7:1

Fuel System DFI® with two 36mm Mikuni throttle bodies

Ignition TCBI with electronic advance

Starting System Electric

Transmission Automatic CVT with centrifugal clutch (H,L,N,R)

Final Drive Selectable 2WD/4WD with locking front differential,

shaft

Engine Braking Yes

Rear Brakes Sealed, oil-bathed, multi-disc

Ground Clearance 11.2 in

Fuel Capacity 7.9 gal

Turning Radius 16.7 ft

Cargo Bed 27.6 x 43.3 x 10.4 in Dimensions (LxWxH)

Cargo Bed Load

Capacity

600 lb

Payload Capacity 1109 lb

Seating Capacity 2

Towing Capacity 1300 lb

Lighting (2) headlights, (2) taillights, stoplight

## **CAPABILITY**

Front Suspension / Wheel Travel

Double Wishbone; Fox Podium coil-over shocks with piggyback reservoir, adjustable preload and 24-way

Rear Suspension /

Wheel Travel

compression damping/8.0 in.

Double Wishbone; Fox Podium coil-over shocks with

piggyback reservoir, adjustable preload and 24-way compression damping/8.3 in.

Front Tires Maxxis 26 x 9-12

Rear Tires Maxxis 26 x 11-12

Steering Electric Power Steering (EPS) / rack-and-pinion

Front Brakes Dual hydraulic discs with two-piston calipers

## **DETAILS**

Frame Steel Tube Double-X Reinforcement

Overall Length 118.1 in
Overall Width 60.0 in

Overall Height 75.8 in

Curb Weight 1570.0 lb\*

Wheelbase 85.8 in

Instruments Multi-function digital met

Multi-function digital meter with speedometer, fuel gauge, clock, hour meter, odometer, dual trip meter and parking-brake indicator, R/N/P/4WD, water temp and

low-oil-pressure indicators

Color Choices Vibrant Blue

Warranty Kawasaki 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

