

NEW 2021

TERYX KRX® 1000 eS



METALLIC ONYX BLACK



POWER

Engine	4-stroke, DOHC, 8-valve parallel-twin, liquid cooled
Displacement	999cc
Maximum Torque	76.7 lb-ft @ 7000 rpm
Bore x Stroke	92.0 x 75.1 mm
Compression Ratio	11.5:1
Fuel System	DFI with two 50mm throttle bodies
Ignition	TCBI with electronic advance
Starting System	Electric
Transmission	Automatic CVT with centrifugal clutch (H,L,N,R)
Final Drive	Selectable 2WD/4WD with locking front differential, shaft
Engine Braking	Yes

Turning Radius	20.3 ft
Cargo Bed Dimensions (LxWxH)	14.6 x 33.1 x 9.1 in
Cargo Bed Load Capacity	351 lbs
Payload Capacity	781 lbs
Seating Capacity	2
Towing Capacity	N/A
Lighting	(2) LED headlights, (2) LED taillights, LED stoplight

CAPABILITY

Front Suspension / Wheel Travel	Double wishbone, FOX 2.5 Podium Live Valve Internal Bypass shocks with piggyback reservoir, fully adjustable preload, and KECS controlled compression damping/18.6 in.
Rear Suspension / Wheel Travel	4-link trailing-arm rear suspension, FOX 2.5 Podium Live Valve Internal Bypass shocks with piggyback reservoir, fully adjustable preload, and KECS controlled compression damping/21.1 in.
Front Tires	MAXXIS Carnivore 31 x 10.00R15 8PR
Rear Tires	MAXXIS Carnivore 31 x 10.00R15 8PR
Steering	Electric Power Steering (EPS) / rack-and-pinion
Front Brakes	Dual hydraulic discs with two-piston calipers
Rear Brakes	Dual hydraulic discs with single-piston calipers
Standard Ground Clearance/Maximum Ground Clearance†	14.0 in / 14.4 in
Fuel Capacity	10.6 gal

DETAILS

Frame	Ladder type, tubular steel
Overall Length	132.1 in
Overall Width	68.1 in
Overall Height	77.0 in
Curb Weight	1944.8 lbs (1947.0 CA)*
Wheelbase	98.8 in
Instruments	Multi-function digital meter with high-grade full-color TFT LCD screen that offers three selectable display modes (Digital, Analogue, Simple) and can auto adjust screen brightness to suit available light. Display functions include speedometer, tachometer, fuel gauge, gear indicator (L, H, N, R), driving mode (2WD/4WD/4WD+Diff Lock), power mode (Full/Low), suspension mode (Soft/Normal/Firm), clock, CVT temperature, digital tachometer, odometer, dual trip meters, total time, trip time, average speed, water temperature, battery voltage, Bluetooth indicator, telephone call indicator, main indicator, economical riding indicator, maintenance reminder, neutral indicator, reverse indicator, headlight high-beam indicator, battery warning lamp, EPS warning lamp, CVT belt warning lamp, seatbelt warning lamp, parking indicator lamp, oil warning lamp, water temperature warning lamp, engine check lamp.
Wheel Type	Alloy with bead-lock wheels
Color Choices	Metallic Onyx Black
Warranty	6 months

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit hawaii.kawasaki.com for full product details.