VULCAN® 900 CLASSIC









POWER

Engine 4-stroke, 55-degree V-twin, liquid-cooled

Displacement 903cc/55.10 cu in

9.5:1

Bore x Stroke 88.0 x 74.2mm

Compression

Ratio

Maximum **Torque**

58.2 lb-ft @ 3,500 rpm

Fuel System

DFI® with 34mm throttle bodies (2), with sub-throttle valves

Ignition

TCBI with Electronic Advance

Transmission

5-speed with positive neutral finder

Final Drive

Kevlar-reinforced belt

PERFORMANCE

Front Suspension / **Wheel Travel** 41mm Showa telescopic fork/5.9 in

Rear Suspension / **Wheel Travel** Uni-Trak® swingarm, 7-way adjustable

spring preload/4.1 in

Front Tire 130/90-16

Rear Tire 180/70-15

Front Brakes Single 300mm hydraulic disc

Rear Brakes Single 270mm hydraulic disc

DETAILS

Semi-double cradle, high-tensile steel **Frame Type**

Rake/Trail 32°/6.3 in

Overall Length 97.0 in

Overall Width 39.6 in

Overall Height 41.9 in

Ground Clearance 5.3 in

26.8 in **Seat Height**

Curb Weight 619.6 lb*

Fuel Capacity 5.3 gal

Wheelbase 64.8 in

Color Choices Pearl Storm Gray/Pearl Robotic White

Warranty 12 Month Limited Warranty



