KLX®230 S









POWER

Engine 4-stroke single, SOHC, air-cooled

Displacement 233cc

Bore x Stroke 67.0 x 66.0mm

Compression

Ratio

Maximum

Torque

13.2 lb-ft @ 6,400 rpm

Fuel System DFI® with 32mm throttle body

9.4:1

Ignition TCBI with Electronic Advance

Transmission 6-speed

Final Drive Sealed chain

Electronic Rider

Aids

Anti-lock Brake System (ABS)

PERFORMANCE

Front
Suspension /
Wheel Travel

Rear Suspension
/ Wheel Travel

Uni-Trak® linkage system and single shock with adjustable spring preload/8.7 in

Front Tire

2.75 x 21

Front Brakes Single 240mm (265mm ABS Model) petal disc with a dual-piston caliper (and ABS)

Rear Brakes Single 220mm petal disc with single-piston

caliper (and ABS)

DETAILS

Frame Type Perimeter, high-tensile steel

Rake/Trail 24.6°/3.7 in

Overall Length 81.8 in

Overall Width 33.2 in

Overall Height 44.8 in

Ground 9.4 in Clearance

Seat Height 33.2 in

Curb Weight 291.0/293.2 lb* 50-State Model

Fuel Capacity 2.0 gal

Wheelbase 53.7 in

Special Features | ERGO-FIT®, LCD Instrumentation with

Smartphone Connectivity via RIDEOLOGY THE

APP MOTORCYCLE

Color Choices Lime Green, Battle Gray

Warranty 12 Month Limited Warranty

Scan with camera to view videos, key features and more.

Rear Tire



4.10 x 18