KLX[®]230 S









P	N	V	N	F	R
	u		м	L	

Engine 4-stroke single, SOHC, air-cooled

Displacement 233cc

67.0 x 66.0mm **Bore x Stroke**

Compression

Ratio

9.4:1

Maximum **Torque**

13.2 lb-ft @ 6,400 rpm

Fuel System

DFI® with 32mm throttle body

Ignition

TCBI with Electronic Advance

Transmission

6-speed

Final Drive

Sealed chain

Electronic Rider

Aids

Anti-lock Brake System (ABS)

PERFORMANCE

Front Suspension / **Wheel Travel**

37mm telescopic fork/7.8 in

Rear Suspension / Wheel Travel

Uni-Trak® linkage system and single shock with adjustable spring preload/8.7 in

Front Tire 2.75 x 21

4.10 x 18

Single 240mm (265mm ABS Model) petal disc **Front Brakes** with a dual-piston caliper (and ABS)

Single 220mm petal disc with single-piston **Rear Brakes** caliper (and ABS)

DETAILS

Perimeter, high-tensile steel **Frame Type**

24.6°/3.7 in Rake/Trail

Overall Length 81.8 in

Overall Width 33.2 in

Overall Height 44.8 in

9.4 in Ground

Clearance

Seat Height 33.2 in

Curb Weight 291.0/293.2 lb* 50-State Model

Fuel Capacity 2.0 gal

Wheelbase 53.7 in

Special Features ERGO-FIT®, LCD Instrumentation with

Smartphone Connectivity via RIDEOLOGY THE

APP MOTORCYCLE

Color Choices Lime Green, Battle Gray

Warranty 12 Month Limited Warranty



Rear Tire

