
KLX[®]300









P	N	W	II	FI	R
	U	М	и	ы	A

Engine 4-stroke single, DOHC, liquid-cooled

Displacement 292cc

Bore x Stroke 78.0 x 61.2mm

Compression

Ratio

DFI® with 34mm Keihin throttle body **Fuel System**

11.1:1

CDI Ignition

Transmission 6-speed, return shift with wet multi-disc

manual clutch

Final Drive Chain

Front Brakes

Single 250mm petal disc with a dual-piston

caliper

Rear Brakes Single 240mm petal disc with single-piston

caliper

PERFORMANCE

43mm inverted cartridge fork with adjustable **Front** Suspension / compression damping /10.0 in **Wheel Travel**

Rear Suspension / Wheel Travel

Uni-Trak® gas charged shock with piggyback reservoir with adjustable compression, rebound damping and spring preload/9.1 in

Front Tire

3.00 x 21

Rear Tire

4.6 x 18

DETAILS

Tubular, Semi Double Cradle **Frame Type**

26.7° / 4.2 in Rake/Trail

Overall Length 85.6 in

Overall Width 32.3 in

Overall Height 46.7 in

Ground 10.8 in Clearance

Seat Height 35.2 in

Curb Weight 302.1 lb*

Fuel Capacity 2.0 gal

Wheelbase 56.7 in

Color Choices Lime Green, Battle Gray, Cypher Camo Gray

(Matte)

Warranty 12 Months

Kawasaki **Protection** Plus™ (optional) 12, 24, 36, or 48 months



