## KLX®300SM









## **POWER**

4-stroke single, DOHC, liquid-cooled **Engine** 

**Displacement** 292cc

**Bore x Stroke** 78.0 x 61.2mm

Compression

Ratio

11.1:1

**Fuel System** DFI® with 34mm Keihin throttle body

Ignition CDI

6-speed, return shift with wet multi-disc **Transmission** 

manual clutch

**Final Drive** Chain **Rear Brakes** 

**Front Brakes** 

Single 300mm petal disc with a dual-piston

caliper

Single 240mm petal disc with single-piston

## **PERFORMANCE**

43mm inverted cartridge fork with adjustable **Front** Suspension / compression damping / 9.1 in **Wheel Travel** 

Uni-Trak® gas charged shock with piggyback Rear reservoir with adjustable rebound damping Suspension / **Wheel Travel** and spring preload/8.1 in

**Front Tire** 110/70-17

**Rear Tire** 130/70-17

## **DETAILS**

**Frame Type** Semi Double Cradle

25.0°/2.8 in Rake/Trail

**Overall Length** 83.3 in

**Overall Width** 31.1 in

**Overall Height** 44.7 in

Ground 9.3 in

Clearance

**Seat Height** 

**Curb Weight** 

Plus™ (optional)

**Fuel Capacity** 2.0 gal

Wheelbase 56.5 in

**Color Choices** Battle Gray, Phantom Blue

33.9 in

304.3 lb\*

12 Month Limited Warranty Warranty

Kawasaki 12, 24, 36, or 48 months **Protection** 



