KX[™]250X







POWER		
Engine	4-stroke single, DOHC, liquid-cooled	
Displacement	249cc	
Bore x Stroke	78.0 x 52.2mm	
Compression Ratio	14.1:1	
Fuel System	DFI® with 44mm Keihin throttle body and dual injectors	
Ignition	Digital CDI	
Transmission	5-speed, return shift, with wet multi-disc manual clutch	
Final Drive	Chain	

DETAILS	
Rear Brakes	Single 240mm Braking petal disc with single- piston caliper
Front Brakes	Single semi-floating 270mm Braking petal disc with dual-piston caliper

110/100-18

PERFORMANCE			
Electronic Rider Aids	Launch Control Mode		
Final Drive	Chain		
Transmission	5-speed, return shift, with wet multi-disc manual clutch		
Ignition	Digital CDI		
Fuel System	DFI® with 44mm Keihin throttle body and dual injectors		
Ratio	14.1.1		

DLIAILO		
Frame Type	Aluminum perimeter	
Rake/Trail	27.8° /4.8 in	
Overall Length	85.4 in	
Overall Width	32.3 in	
Overall Height	49.6 in	
Ground Clearance	13.0 in	
Seat Height	37.2 in	
Curb Weight	230.1 lb* without fuel / 240.2 lb*	
Fuel Capacity	1.64 gal	
Wheelbase	58.3 in	
Color Choices	Lime Green	
Warranty	Not Available	
Kawasaki Protection Plus™ (optional)	Not Available	

Front Suspension / **Wheel Travel** 48mm inverted telescopic coil-spring fork with 23-way compression damping and 20-way rebound damping/12.4 in

Rear Suspension / Wheel Travel

Uni-Trak® with dual-range (2.25 turns high speed/21-way low-speed) compression damping, 38-way rebound damping and adjustable preload/12.4 in

Front Tire

80/100-21





Rear Tire