





	0	V	M		
r	u	ľ	۷	Ŀ	K

Engine 2-stroke single, liquid-cooled

Displacement 64cc

Bore x Stroke 44.5 x 41.6mm

Compression

Ratio

Fuel System 24mm Mikuni carburetor

8.4:1

Ignition CDI with Digital Advance

Transmission 6-speed, return shift, with wet multi-disc

manual clutch

Final Drive Chain

PERFORMANCE

Front 33mm leading axle telescopic fork with 4-Suspension / way rebound damping/8.3 in

Rear Uni-Trak® single shock system with stepless 3-turns rebound damping and fully adjustable spring preload/9.4 in

, i

Rear Tire 80/100-12

Front Brakes Single 180mm disc with single-piston caliper

Rear Brakes Single 180mm disc with single-piston caliper

DETAILS

Frame Type	High-tensile steel semi-double cradle
Rake/Trail	27° / 2.4 in
Overall Length	62.6 in
Overall Width	29.9 in
Overall Height	37.6 in
Ground Clearance	12.0 in
Seat Height	29.9 in
Curb Weight	132.2 lb*
Fuel Capacity	1.0 gal

Warranty

Wheelbase

Color Choices

Kawasaki Protection Plus™ (optional) Lime Green

44.1 in

Not Available

Not Available



Front Tire



60/100-14