MULE PRO-FXR™ 1000 LE







POWER

Engine 4-stroke, 2-cylinder, DOHC, liquid-cooled, gas

Displacement 999cc

Maximum Torque 61.5 lb-ft

Bore x Stroke 92.0 x 75.1mm

Compression Ratio 10.1:1

DFI® with 38mm throttle body **Fuel System**

90 amp

Continuously Variable Transmission (CVT) with (L,H,N,R) **Transmission**

Final Drive Selectable 2WD/4WD, shaft Dual mode rear differential

with differential lock

Engine Braking Yes

Alternator Output

(max)

CAPABILITY

Double wishbone/11.0 in Front Suspension / **Wheel Travel**

Rear Suspension / Double wishbone/10.1 in Wheel Travel

Front Tires 27 x 9.00-12, radial **Rear Tires** 27 x 11.00-12, radial

Steering Electric Power Steering (EPS), Tilt steering

Park Brake Type Independent, Mechanical Disc

Front Brakes Dual Disc, 2 piston caliper

Rear Brakes Dual Disc, 1 piston caliper **Ground Clearance** 13.2 in (max), 12.2 in (std)

Fuel Capacity 7.9 gal **Turning Radius** 14.0 ft

Cargo Bed 37.6 x 53.3 x 11.0 in **Dimensions (LxWxH)**

Cargo Bed Load 999 lb / 600.0 lb CA Model Capacity

Payload Capacity 1,616.3 lb / 1,263.5 lb CA Model

Seating Capacity

Towing Capacity 2.000 lb

Lighting (2) Halogen headlights. (2) LED headlights

DETAILS

Overall Length 122.0 in **Overall Width** 64.0 in **Overall Height** 78.5 in

Curb Weight 1,746.4 lb* / 1,748.6 lb* CA Model

Wheelbase 79.7 in

Instruments Multi-function display includes digital speedometer, fuel

gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse

and parking indicators, seatbelt reminder lamps

Additional Features Roof, Rear Bumper, Contoured Two-Tone Bench Seat, **Additional Cup Holders**

Color Choices

Ice Grav

Warranty Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

