MULE PRO-FXT™ 1000 LE RANCH EDITION







POWER

Engine 4-stroke, 2-cylinder, DOHC, liquid-cooled, gas

Displacement 999cc

Maximum Torque 61.5 lb-ft

Bore x Stroke 92.0 x 75.1mm

Compression Ratio 10.1:1

DFI® with 38mm throttle body **Fuel System**

Continuously Variable Transmission (CVT) with (L,H,N,R) **Transmission**

Final Drive Selectable 2WD/4WD, shaft Dual mode rear differential

with differential lock

Engine Braking Yes

(max)

Alternator Output 90 amp

CAPABILITY

Double wishbone/11.0 in Front Suspension / **Wheel Travel**

Rear Suspension / Double wishbone/10.1 in

Wheel Travel

Front Tires 26 x 9.00-12, radial **Rear Tires** 26 x 11.00-12, radial

Steering Electric Power Steering (EPS), Tilt steering

Park Brake Type Independent, Mechanical Disc

Front Brakes Dual Disc, 2 piston caliper

Rear Brakes Dual Disc, 1 piston caliper **Ground Clearance** 12.6 in (max), 11.6 in (std)

Fuel Capacity 7.9 gal **Turning Radius** 16.0 ft

Cargo Bed 42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-Dimensions (LxWxH)

person)

Cargo Bed Load

Capacity

999 lb (3-person) / 350 lb (6-person) / 348 lb CA Model

Payload Capacity 1,616.3 lb / 1,263.5 lb CA Model

Seating Capacity 3-person (1 row), 6 person (2 row)

Towing Capacity 2.000 lb

Lighting (2) Halogen headlights. (2) LED headlights

DETAILS

Overall Length 135.8 in

Overall Width 64.0 in

Overall Height 80.9 in

Curb Weight 1,966.9 lb* / 1,969.1 lb* CA Model

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer, fuel

gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse

and parking indicators, seatbelt reminder lamps

Additional Features Roof, Additional Front Cup Holders, WARN® VRX 45 Winch,

Premium Seats, Self-Leveling Rear Suspension

Color Choices Metallic Titanium

Warranty Kawasaki STRONG 3-Year Limited Warranty



