NINJA® ZX™-10R









POWER

4-stroke, In-Line Four, DOHC, 16-valve, liquid-**Engine**

cooled

13.0:1

998cc **Displacement**

76.0 x 55.0mm **Bore x Stroke**

Compression

Ratio

DFI® with 47mm throttle bodies **Fuel System**

Ignition TCBI with Digital Advance

Transmission 6-speed, return shift

Final Drive Sealed chain

Electronic Rider

Aids

Öhlins Electronic Steering Damper, Electronic Cruise Control, Power Modes, Kawasaki Launch Control Mode (KLCM), Kawasaki Intelligent antilock Brake System (KIBS) (ABS only), Sport-Kawasaki TRaction Control (S-KTRC), Kawasaki Engine Braking Control, Kawasaki Quick Shifter (KQS) (upshift & downshift), Kawasaki Corner

Management Function (KCMF)

PERFORMANCE

Front Suspension / Wheel Travel

43mm inverted Balance Free Fork, adjustable stepless rebound and compression damping, spring preload adjustability/4.7 in

Rear Suspension / Wheel Travel

Horizontal back-link with Balance Free gascharged shock, adjustable compression damping, adjustable rebound damping, stepless adjustable spring preload/4.5 in

Front Tire 120/70 ZR17

Rear Tire 190/55 ZR17

Front Brakes Brembo dual semi-floating 330mm discs with dual

radial mounted monobloc 4-piston calipers, Kawasaki Intelligent anti-lock Brake System (KIBS)

(ABS only)

Single 220mm disc with aluminum single-piston **Rear Brakes**

caliper, Kawasaki Intelligent anti-lock Brake

System (KIBS) (ABS only)

DETAILS

Frame Type Aluminum perimeter

Rake/Trail 25.0°/4.1 in

Overall Length 82.1 in

Overall Width 29.5 in

Overall Height 46.7 in

Ground Clearance 5.3 in

Seat Height 32.9 in

Curb Weight 456.4 lb* (ABS), 452.0 lb* (non-ABS)

Fuel Capacity 4.5 gal

Wheelbase 57.1 in

Special Features 4.3" Full-Color TFT Instrumentation, Smartphone

Connectivity via RIDEOLOGY THE APP

Color Choices Metallic Flat Spark Black/Ebony

12 Month Limited Warranty Warranty

Scan with camera to view videos. key features and more.

