## TERYX4™ S CAMO









## **POWER**

Engine 4-stroke, SOHC, 4-valve V-twin, liquid-cooled

Displacement 783cc

Maximum Torque 47.0 lb-ft @ 5,500 rpm

Bore x Stroke 85.0 x 69.0mm

Compression Ratio 10.7:1

Fuel System DFI® with two 36mm Mikuni throttle bodies

Ignition TCBI with Electronic Advance

Starting System Electric

Transmission Automatic CVT with centrifugal clutch (H,L,N,R)

Final Drive Selectable 2WD/4WD with locking front differential,

shaft

Engine Braking Yes

Ground Clearance 12.2 in (max) / 11.2 in (std)

Fuel Capacity 7.9 gal

Turning Radius 17.7 ft

Cargo Bed Dimensions (LxWxH) 17.9 x 47.6 x 8.7 in

Cargo Bed Load

Capacity

249 lb

Payload Capacity 1,000 lb

Seating Capacity 4

Towing Capacity 1,300 lb

Lighting (4) LED headlights, (2) LED taillights, LED stoplight

## CAPABILITY

Front Suspension / Double v Wheel Travel adjustable

Double wishbone, FOX 2.0 LSC Piggyback Shocks, fully adjustable preload, and adjustable compression

damping/10.7 in

Rear Suspension / Wheel Travel Double wishbone, FOX 2.0 LSC Piggyback Shocks, fully adjustable preload, and adjustable compression

damping/10.0 in

Front Tires Maxxis® 27 x 9-14

Rear Tires Maxxis® 27 x 11-14

Steering Electric Power Steering (EPS) / rack-and-pinion

Front Brakes Dual hydraulic discs with two-piston calipers

Rear Brakes Sealed, oil-bathed, multi-disc

## **DETAILS**

**Overall Width** 

Frame Steel Tube Double-X Reinforcement

Overall Length 125.4 in

Overall Height 80.5 in

Curb Weight 1,638.3 lb\* / 1,640.5 lb\* CA Model

62.6 in

Wheelbase 88.2 in

**Instruments** Multi-function digital meter with speedometer, fuel

gauge, clock, hour meter, odometer, dual trip meter and parking-brake indicator, R/N/P/4WD, water temp

and low-oil-pressure indicators

Additional Features Roof

Color Choices TRUETIMBER® STRATA

Warranty Kawasaki Strong 3-Year Limited Warranty



