



2024

# VULCAN® S

**Kawasaki**  
Let the Good Times Roll®



-  PEARL SAND KHAKI/EBONY
-  METALLIC FLAT SPARK BLACK



POWER		Front Tire	120/70x18
Engine	4-stroke, 2-cylinder, DOHC, liquid-cooled	Rear Tire	160/60x17
Displacement	649cc	Front Brakes	Single 300mm disc with twin-piston caliper, (and ABS)
Bore x Stroke	83.0 x 60.0mm	Rear Brakes	Single 250mm disc with single-piston caliper (and ABS)
Compression Ratio	10.8:1	DETAILS	
Maximum Torque	46.3 lb-ft @ 6,600 rpm	Frame Type	High-tensile steel diamond frame
Fuel System	DFI® with 38mm throttle bodies (2), with sub-throttle valves	Rake/Trail	31° / 4.7 in
Ignition	TCBI with Electronic Advance	Overall Length	90.9 in
Transmission	6-speed with positive neutral finder	Overall Width	34.6 in
Final Drive	Sealed chain	Overall Height	43.3 in
Electronic Rider Aids	Economical Riding Indicator, Anti-lock Brake System (ABS)	Ground Clearance	5.1 in
PERFORMANCE		Seat Height	27.8 in
Front Suspension / Wheel Travel	41mm telescopic fork/5.1 in	Curb Weight	498.3 lb* (ABS), 491.7 lb* (non-ABS)
Rear Suspension / Wheel Travel	Lay-down offset rear shock with linkage and adjustable preload/3.2 in	Fuel Capacity	3.7 gal
		Wheelbase	62.0 in
		Color Choices	Pearl Sand Khaki/Ebony, Metallic Flat Spark Black
		Warranty	12 Month Limited Warranty

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [hawaii.kawasaki.com](http://hawaii.kawasaki.com) for full product details.