DOWED

VULCAN® S CAFE ABS







PUWER		
Engine	4-stroke, 2-cylinder, DOHC, liquid-cooled	
Displacement	649cc	
Bore x Stroke	83.0 x 60.0mm	
Compression Ratio	10.8:1	
Maximum Torque	46.3 lb-ft @ 6,600 rpm	
Fuel System	DFI® with 38mm throttle bodies (2), with sub-	

Ratio	
Maximum Torque	46.3 lb-ft @ 6,600 rpm
Fuel System	DFI® with 38mm throttle bodies (2), with subthrottle valves
Ignition	TCBI with Electronic Advance
Transmission	6-speed with positive neutral finder
Final Drive	Sealed chain
Electronic Rider Aids	Economical Riding Indicator, Anti-lock Brake System (ABS)

Electronic Rider Aids	Economical Riding Indicator, Anti-lock Brake System (ABS)	
PERFORMANCE		
Front Suspension / Wheel Travel	41mm telescopic fork/5.1 in	
Rear Suspension / Wheel Travel	Lay-down offset rear shock with linkage and adjustable preload/3.2 in	

Front Tire	120/70x18
Rear Tire	160/60x17
Front Brakes	Single 300mm disc with twin-piston caliper, ABS
Rear Brakes	Single 250mm disc with single-piston caliper,

	Front Brakes	Single 300mm disc with twin-piston caliper, ABS
	Rear Brakes	Single 250mm disc with single-piston caliper, ABS
DETAILS		
	Frame Type	High-tensile steel diamond frame

Frame Type	High-tensile steel diamond frame
Rake/Trail	31° / 4.7 in
Overall Length	90.9 in
Overall Width	34.6 in
Overall Height	44.5 in
Ground Clearance	5.1 in
Seat Height	27.8 in
Curb Weight	502.7 lb*
Fuel Capacity	3.7 gal
Wheelbase	62.0 in
Color Choices	Metallic Matte Dark Gray/Metallic Flat Spark Black
Warranty	12 Month Limited Warranty



