

2024

# Z650RS ABS



 EBONY/METALLIC MATTE CARBON GRAY



POWER		Rear Suspension / Wheel Travel	
Engine	4-stroke, 2-cylinder, DOHC, liquid-cooled	Front Tire	Horizontal back-link with adjustable preload, swingarm/5.1 in
Displacement	649cc	Rear Tire	120/70 ZR17
Bore x Stroke	83.0 x 60.0mm	Front Brakes	160/60 ZR17
Compression Ratio	10.8:1	Rear Brakes	Dual 300mm petal-style discs with two-piston calipers, ABS
Maximum Torque	48.5 lb-ft @ 6,500 rpm		Single 220mm petal-style disc, ABS
Fuel System	DFI® with Keihin 36mm throttle bodies	DETAILS	
Ignition	TCBI with Electronic Advance	Frame Type	Trellis, high tensile steel
Transmission	6-speed, return shift	Rake/Trail	24.0° / 3.9 in
Final Drive	Sealed chain	Overall Length	81.3 in
Electronic Rider Aids	Economical Riding Indicator, Kawasaki TRaction Control (KTRC - 3 Modes), Anti-lock Brake System (ABS)	Overall Width	31.5 in
PERFORMANCE		Overall Height	43.9 in
Front Suspension / Wheel Travel	Telescopic fork/4.9 in	Ground Clearance	4.9 in
		Seat Height	31.5 in
		Curb Weight	412.3 lb*
		Fuel Capacity	3.2 gal
		Wheelbase	55.3 in
		Color Choices	Ebony/Metallic Matte Carbon Gray
		Warranty	12 Month Limited Warranty

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [hawaii.kawasaki.com](http://hawaii.kawasaki.com) for full product details.