VULCAN® 1700 VOYAGER® ABS









D	N	W	ľC	D
Г	U	W	ľ	П

Engine 4-stroke, 52-degree V-twin, liquid-cooled

Displacement 1,700cc

Bore x Stroke 102.0 x 104.0mm

Compression 9.5:1

Ratio

Maximum

107.6 lb-ft @ 2,750 rpm

Torque

Fuel System DFI® with 42mm throttle bodies (2)

Ignition TCBI with Electronic Advance

Transmission 6-speed with overdrive and positive neutral

finder

Final Drive Carbon fiber-reinforced belt

Electronic Rider
Aids
Electronic Cruise Control, Kawasaki Advanced
Coactive-Braking Technology (K-ACT) ABS

PERFORMANCE

Front
Suspension /
Wheel Travel

45mm Showa telescopic fork/5.5 in

Rear Suspension / Wheel Travel

Swingarm with twin air-assisted shocks, with 4-way adjustable rebound damping/3.1 in

Front Tire 130/90-16

Rear Tire 170/70-16

Front Brakes Dual 300mm discs, dual four-piston calipers,

K-ACT ABS

Rear Brakes Single 300mm disc, twin-piston caliper, K-ACT

ABS

DETAILS

Frame Type Steel, double-cradle with box-section singletube backbone

Rake/Trail 30°/7.0 in

Overall Length 100.8 in

Overall Width 39.2 in

Overall Height 61.0 in

Ground 5.3 in Clearance

Seat Height 28.7 in

Curb Weight 895.2 lb*

Fuel Capacity 5.3 gal

Wheelbase 65.6 in

Special Features Integrated audio system v

Integrated audio system with SiriusXM and

intercom headset compatibility

Color Choices Metallic Ocean Blue/Metallic Moondust Gray

Warranty 36 Month Limited Warranty



