KLX®110R L









90mm mechanical drum, cable actuated

110mm mechanical drum, rod actuated

2.50 x 14

3.00 x 12

POWER

Engine 4-stroke, single-cylinder, SOHC, air-cooled

Displacement 112cc

Bore x Stroke 53.0 x 50.6mm

Compression Ratio 9.5:1

Fuel System Keihin PB18 carburetor and screw type throttle limiter on grip housing

Ignition DC-CDI

Transmission 4-speed, return shift, wet multi-disc

manual clutch

Final Drive Chain

DETAILS

Front Tire

Rear Tire

Front Brakes

Rear Brakes

Backbone frame, high-tensile steel **Frame Type** 24.2°/1.9 in Rake/Trail **Overall Length** 61.4 in **Overall Width** 25.6 in **Overall Height** 39.0 in 10.4 in Ground Clearance **Seat Height** 28.7 in **Curb Weight** 167.5 lb* **Fuel Capacity** 1.0 gal

Lime Green, Battle Gray

6 Month Limited Warranty

42.3 in

PERFORMANCE

Suspension /
Wheel Travel

Rear Swingarm with single hydraulic shock/5.2
in

30mm hydraulic telescopic fork/5.5 in



Wheel Travel

Front



Wheelbase

Warranty

Color Choices