KLX®230 S









D	n	V	V	С	D
Г	U	V	V	C	π

4-stroke single, SOHC, air-cooled

Displacement 233cc

Bore x Stroke 67.0 x 66.0mm

Compression

Ratio

Engine

9.4:1

Maximum Torque 13.0 lb-ft @ 6,400 rpm

Fuel System DFI® with 32mm throttle body

Ignition TCBI with Electronic Advance

Transmission 6-speed

Final Drive Sealed chain

Electronic Rider

Aids

Rear Brakes

Single 220mm petal disc with single-piston caliper (and ABS)

DETAILS

Frame Type Perimeter, high-tensile steel

Rake/Trail 24.6°/3.8 in

Overall Length 81.9 in

Overall Width 33.3 in

Overall Height 44.9 in

Ground

Clearance

9.4 in

Seat Height 33.3 in

Estimated Dry

Weight

275.6 lb** (ABS), 273.4 lb** (non-ABS) / 277.7 lb** (ABS), 275.5 lb** (non-ABS) 50-State Model

Curb Weight 291.1 lb* (ABS), 288.9 lb* (non-ABS) / 293.3 lb*

(ABS), 291.1 lb* (non-ABS) 50-State Model

Fuel Capacity 2.0 gal

Wheelbase 53.7 in

Smartphone Connectivity via RIDEOLOGY THE

APP MOTORCYCLE

Color Choices

Lime Green

Warranty

12 Month Limited Warranty

PERFORMANCE

Front Suspension / Wheel Travel

Rear Suspension / Wheel Travel

Uni-Trak® linkage system and single shock with adjustable spring preload/8.8 in

Front Tire 2.75 x 21

Rear Tire 4.10 x 18

Front Brakes Single 240mm (265mm ABS Model) petal disc with a dual-piston caliper (and ABS)

Anti-lock Brake System (ABS)



