KLX®230 S







caliper (and ABS)

POWER		
Engine	4-stroke single, SOHC, air-cooled	
Displacement	233cc	
Bore x Stroke	67.0 x 66.0mm	
Compression Ratio	9.4:1	
Maximum Torque	13.0 lb-ft @ 6,400 rpm	
Fuel System	DFI® with 32mm throttle body	
Ignition	TCBI with Electronic Advance	
Transmission	6-speed	
Final Drive	Sealed chain	
Electronic Rider Aids	Anti-lock Brake System (ABS)	

DETAILS	
Frame Type	Perimeter, high-tensile steel
Rake/Trail	24.6°/3.8 in
Overall Length	81.9 in
Overall Width	33.3 in
Overall Height	44.9 in
Ground Clearance	9.4 in
Seat Height	33.3 in
Estimated Dry Weight	275.6 lb** (ABS), 273.4 lb** (non-ABS) / 277.7 lb** (ABS), 275.5 lb** (non-ABS) 50-State Model
Curb Weight	291.1 lb* (ABS), 288.9 lb* (non-ABS) / 293.3 lb* (ABS), 291.1 lb* (non-ABS) 50-State Model
Fuel Capacity	2.0 gal
Wheelbase	53.7 in

ERGO-FIT®, LCD Instrumentation with

APP MOTORCYCLE

12 Month Limited Warranty

Lime Green


Smartphone Connectivity via RIDEOLOGY THE

Single 220mm petal disc with single-piston

PERFORMANCE

Front Suspension / Wheel Travel	37mm telescopic fork/7.9 in
Rear Suspension / Wheel Travel	Uni-Trak® linkage system and single shock with adjustable spring preload/8.8 in
Front Tire	2.75 x 21
Rear Tire	4.10 x 18
Front Brakes	Single 240mm (265mm ABS Model) petal disc with a dual-piston caliper (and ABS)





Special Features

Color Choices

Warranty

Rear Brakes