KLX®230SM ABS







P	O	W	F	R
	w			

Engine 4-stroke single, SOHC, air-cooled

Displacement 233cc

Bore x Stroke 67.0 x 66.0mm

Compression

Ratio

9.4:1

Maximum Torque 13.0 lb-ft @ 6,400 rpm

Fuel System DFI® with 32mm throttle body

Ignition TCBI with Electronic Advance

Transmission 6-speed

Final Drive Sealed chain

Electronic Rider

Aids

Front Brakes

Single 300mm petal disc with a dual-piston

caliper and ABS

Rear Brakes Single 220mm petal disc with single-piston

caliper and ABS

DETAILS

Frame Type Perimeter, high-tensile steel

Rake/Trail 24.9°/3.0 in

Overall Length 80.1 in

Overall Width 33.3 in

Overall Height 44.3 in

Ground Clearance 8.7 in

Seat Height 33.1 in

Estimated Dry

Weight

284.4/286.5 lb** 50-State Model

Curb Weight 299.9/302.1 lb* 50-State Model

Fuel Capacity 2.0 gal

Wheelbase 53.7 in

Special Features ERGO-FIT®, LCD Instrumentation with

Smartphone Connectivity via RIDEOLOGY THE

APP MOTORCYCLE

Color Choices Battle Gray

Warranty 12 Month Limited Warranty

PERFORMANCE

Front Suspension / Wheel Travel

Rear Suspension / Wheel Travel

Uni-Trak® linkage system and single shock with adjustable spring preload/8.8 in

Front Tire 110/70-17

Rear Tire 120/70-17

Anti-lock Brake System (ABS)



