KLX®300SM









POWER

Engine 4-stroke single, DOHC, liquid-cooled

Displacement 292cc

Bore x Stroke 78.0 x 61.2mm

Compression

Ratio

11.1:1

Fuel System DFI® with 34mm Keihin throttle body

Ignition CDI

Transmission 6-speed, return shift with wet multi-disc

manual clutch

Final Drive Chain

Rear Tire 130/70-17

Front Brakes Single 300mm petal disc with a dual-

piston caliper

Rear Brakes Single 240mm petal disc with single-

piston caliper

PERFORMANCE

Front 43mm inverted cartridge fork with adjustable compression damping / 9.1 in Wheel Travel

Rear Suspension / Wheel Travel Uni-Trak® gas charged shock with piggyback reservoir with adjustable rebound damping and spring preload/ 8.1

ın

Front Tire 110/70-17

DETAILS

Frame Type Semi Double Cradle

Rake/Trail 25.0°/2.8 in

Overall Length 83.3 in

Overall Width 31.1 in

Overall Height 44.7 in

Ground 9.3 in Clearance

Seat Height 33.9 in

Curb Weight 304.3 lb*

Fuel Capacity 2.0 gal

Wheelbase 56.5 in

Color Choices Battle Gray, Phantom Blue

Warranty 12 Month Limited Warranty



