







## **POWER**

**Ratio** 

2-stroke, single-cylinder with exhaust power valve (KIPS), liquid-cooled

Displacement 112cc

Bore x Stroke 52.5 x 51.6mm

Compression 9.9

9.9:1 (low speed) / 8.6:1 (high speed)

Fuel System 28mm Keihin carburetor

**Ignition** CDI with Digital Advance

**Transmission** 6-speed, return shift, with wet multi-disc

manual clutch

Final Drive Chain

**Front Brakes** 

Single 220mm petal disc with dual-piston

caliper

**Rear Brakes** Single 184mm petal disc with single-piston

caliper

## **DETAILS**

Frame Type High-tensile steel perimeter design with subframe member

Rake/Trail 29.0°/4.3 in

Overall Length 75.6 in

Overall Width 30.1 in

Overall Height 45.3 in

Ground 13.0 in

Clearance

**Features** 

**Seat Height** 

34.3 in

Curb Weight 169.7 lb\*

Fuel Capacity 1.32 gal

Wheelbase 51.6 in

Special ERGO-FIT®

Color Choices Lime Green

Warranty Not Available

## **PERFORMANCE**

Front
Suspension /
Wheel Travel

36mm inverted telescopic cartridge fork with 20-way compression damping/10.8 in

Rear Suspension / Wheel Travel Uni-Trak® gas charged shock with piggyback reservoir with 24-way compression and 21-way rebound damping plus adjustable spring

preload/10.8 in

**Front Tire** 

70/100-19

**Rear Tire** 

90/100-16



