







| D | N | 1 | M | | D |
|---|---|----|---|---|---|
| | u | V, | N | E | π |

Engine 2-stroke, single-cylinder with exhaust power valve (KIPS), liquid-cooled

Displacement 84cc

Bore x Stroke 48.5 x 45.8mm

Compression Ratio 10.9:1 (low speed) / 9.0:1 (high speed)

Fuel System

28mm Keihin carburetor

Ignition

CDI with Digital Advance

Transmission

6-speed, return shift, with wet multi-disc

manual clutch

Final Drive

Chain

PERFORMANCE

Front Suspension / Wheel Travel 36mm inverted telescopic cartridge fork with 20-way compression damping/10.8 in

Rear Suspension / Wheel Travel Uni-Trak® single shock system with 24-way compression and 21-way rebound damping, plus adjustable spring preload/10.8 in

Front Tire 70/100-17

Rear Tire 90/100-14

Front Brakes

Single 220mm petal disc with dual-piston

caliper

Rear Brakes

Single 184mm petal disc with single-piston

caliper

DETAILS

Frame Type High-tensile steel perimeter design with subframe member

Rake/Trail 29.0°/3.8 in

Overall Length 72.0 in

Overall Width 30.1 in

Overall Height 43.3 in

Ground 11.4 in Clearance

Seat Height 32.7 in

Curb Weight 164.4 lb*

Fuel Capacity 1.32 gal

Wheelbase 49.8 in

Special ERGO-FIT® Features

Color Choices Lime Green

Warranty Not Available

Scan with camera (to view videos, key features and more.

